Technical Datasheet

Product Name: Durable 2K Acrylic Solvent-Free Paint

Product Code: 2TX10 Max



This grade of traffic marking 2k-paints is solvent free, normal dry and has better reflection of light. Because of these specifications this paint is suitable for cross-walks and traffic signs marking. This paint has very good performance in traffic lots.

| Specifications: | | |
|---------------------------------|---|------------|
| • | | ASTM |
| Color: | White, Yellow, Red | EN 1436 |
| Applications: | Line striping Cross walks | |
| Resin: | Acrylic | |
| Gloss: | Opaque | |
| Directional Reflectance: | White 90%(~60% yellow) | E97 |
| Density(gram/cm ³): | 1.7±0.02 | D 1475 |
| Solid by Weight | 99±0.5 | D 1644 |
| Solid by Volume | 98±2 | |
| TiO2 | >8 (white) | |
| Coverage: | 1 m ² /Litter | D344 |
| Thinner | No need for thiner | |
| Curing: | 1.5-2% hardener (BPO) | |
| Water Resistance: | Passes | D870 |
| Skiing Resistance(SRT): | Passes | EN 1436 |
| Resistance over | No change | BS 6044(H) |
| solvents and oil | | |
| Drying Time: | 35 min @ 25° C | D 711 |
| Applying Conditions: | Temperature: 15° C to 25° C | |
| | Surface Temperature: 5° C more than Dew Point | |
| | Moisture: below than 80% | |
| Surface Condition: | Should be without any dust, moisture, oil, grease and any | |
| | extra solid on surface | |
| Applying Methods: | By hand | |
| Storage Condition: | Covered place, Dry and cold, away from sunlight, | |
| | temperature below than 35° C | |
| Better Time to use: | Up to 12 months after production | |
| Safety Attentions: | - Store far from fire, heat, flammable materials | |
| | - In applying in covered places use suitable ventilation | |
| | - Don't use flame near to applying places | |

Asia technology Pioneers Co. Ltd.

Antun Paint Tehran – Iran

Tel: +98 21 88992751 www.AntunPaint.com